## TopTech Tool Manufacturing Inc.



## **Screw Machine Length Drills**

List No. SM02H10 -- M2 Black & Bronze Finish

List No. SM02B10 -- HSS M2 Black Oxide Finish

List No. SM35G10 -- HSS M35 Cobalt Golden Finish



List No. SM42G10 -- HSS M42 Cobalt Golden Finish



#### **Features**

- \* Precision ground to insure concentricity of tip & body
- \* Smooth flutes & special surface treated for effective chip flow
- \* Penetrates faster with less pressure
- \* Premium quality high speed steel, special heat treatment to remain sharper edges, & reduce wear
- \* Self-feeding point, unique flute design and industrial heavy duty web can drill faster, cool, longer!
- \* Cobalt drills have extremely heat resistant
- \* Special bronze-oxide, Tin-Coated, Black Oxide, and bright surface treatment
- \* 3-Equal Flat on shank is for positive holding in 3-Jaw Chucks
- \* All dimensional & element tolerances conform to one of ASME/ANSI B94.11M,

NAS 907 - National Aerospace Standar USCTI - United States Cutting Tool Institute (formerly MCTI)

#### **Design Features**

\* Shank Specification

Drill Size	Shk Dia	Shk Length
Up to 1" inclusive	Same as drill	
Over 1" to 1-1/16"	1"	2"
Over 1-1/16" to 1-1/4"	1"	2-1/4"
Over 1-1/4" to 1-1/2"	1-1/4"	2-1/2"
Over 1-1/2"	1-1/2"	2-1/2"

- \* For sizes under 3/32", a chamfer or male point may be used on end of shank
- \* Chamfer sizes 3/32" and larger at the end of shank
- \* Fully ground drills are also available up to 1" as requests

#### **Application**

- \* Screw Machine drills are popular in the automotive & construction industries. The short flute & overall length provide maximum rigidity. They are often used in screw machinese set-up where spindle clearnace is limited.
- \* 118° allows easier penetration, & 135° Split Point is used with heavier feeds in harder materials
- \* 135° Split Point is popular in hand held drilling to reduce breakage & eliminate skidding or walking
- \* Cobalt drills display higher red hardness & are especially effective in drilling hard/abrasive materials

#### Drills available

Szies: 3/64" to 2-1/2" with fully ground, HSS M2

Standard Drills are Right Hand. Left hand & Parabolic flutes are available as custom request

Drill Sets & Custom Package are available

Material: M2, M35, M42 cobalt HSS

How to Order ....

When order drills, please specify material, diameter, cut direction, surfacef finish, shank style, chisel point angle.

### **Fractional Sizes**

Size	Dec. Equiv	Flute Length	Overall Length	List No
3/64"	0.0469	1/2"	1-3/8"	R/L003
1/16"	0.0625	5/8"	1-5/8"	R/L004
5/64"	0.0781	11/16"	1-11/16"	R/L005
3/32"	0.0938	3/4"	1-3/4"	R/L006
7/64"	0.1094	13/16"	1-13/16"	R/L007
1/8"	0.1250	7/8"	1-7/8"	R/L008

Size	Dec. Equiv	Flute Length	Overall Length	List No
53/64"	0.8281	3-1/2"	5-3/8"	R/L053
27/32"	0.8438	3-1/2"	5-3/8"	R/L054
55/64"	0.8594	3-1/2"	5-1/2"	R/L055
7/8"	0.8750	3-1/2"	5-1/2"	R/L056
57/64"	0.8906	3-5/8"	5-5/8"	R/L057
29/32"	0.9062	3-5/8"	5-5/8"	R/L058



# TopTech Tool Manufacturing Inc.



## **Screw Machine Length Drills**

## **Fractional Sizes**

Size	Dec. Equiv	Flute	Overall	List No
		Length	Length	D/I 000
9/64"	0.1406	15/16" 1"	1-15/16"	R/L009
5/32"	0.1562	•	2-1/16"	R/L010
11/64"	0.1719	1-1/16"	2-1/8"	R/L011
3/16"	0.1875	1-1/8"	2-3/16"	R/L012
13/64"	0.2031	1-3/16"	2-1/4"	R/L013
7/32"	0.2188	1-1/4"	2-3/8"	R/L014
15/64"	0.2344	1-5/16"	2-7/16"	R/L015
1/4"	0.2500	1-3/8"	2-1/2"	R/L016
17/64"	0.2656 0.2812	1-7/16"	2-5/8"	R/L017
9/32"		1-1/2"	2-11/16"	R/L018
19/64"	0.2969	1-9/16"	2-3/4"	R/L019
5/16"	0.3125	1-5/8"	2-13/16"	R/L020
21/64"	0.3281	1-11/16"	2-15/16"	R/L021
11/32"	0.3438	1-11/16"	3"	R/L022
23/64"	0.3594	1-3/4"	3-1/16"	R/L023
3/8"	0.3750	1-13/16"	3-1/8"	R/L024
25/64"	0.3906	1-7/8"	3-1/4"	R/L025
13/32"	0.4062	1-15/16"	3-5/16"	R/L026
27/64"	0.4219	2"	3-3/8"	R/L027
7/16"	0.4375	2-1/16"	3-7/16"	R/L028
29/64"	0.4531	2-1/8"	3-9/16"	R/L029
15/32"	0.4688	2-1/8"	3-5/8"	R/L030
31/64"	0.4844	2-3/16"	3-11/16"	R/L031
1/2"	0.5000	2-1/4"	3-3/4"	R/L032
33/64"	0.5156	2-3/8"	3-7/8"	R/L033
17/32"	0.5312	2-3/8"	3-7/8"	R/L034
35/64"	0.5469	2-1/2"	4"	R/L035
9/16"	0.5625	2-1/2"	4"	R/L036
37/64"	0.5781	2-5/8"	4-1/8"	R/L037
19/32"	0.5938	2-5/8"	4-1/8"	R/L038
39/64"	0.6094	2-3/4"	4-1/4"	R/L039
5/8"	0.6250	2-3/4"	4-1/4"	R/L040
41/64"	0.6406	2-7/8"	4-1/2"	R/L041
21/32"	0.6562	2-7/8"	4-1/2"	R/L042
43/64"	0.6719	2-7/8"	4-5/8"	R/L043
11/16"	0.6875	2-7/8"	4-5/8"	R/L044
45/64"	0.7031	3"	4-3/4"	R/L045
23/32"	0.7188	3"	4-3/4"	R/L046
47/64"	0.7344	3-1/8"	5"	R/L047
3/4"	0.7500	3-1/8"	5"	R/L048
49/64"	0.7656	3-1/4"	5-1/8"	R/L049
25/32"	0.7812	3-1/4"	5-1/8"	R/L050
51/64"	0.7969	3-3/8"	5-1/4"	R/L051
13/16"	0.8125	3-3/8"	5-1/4"	R/L052

S				
Size	Dec. Equiv	Flute	Overall	List No
		Length	Length	
59/64"	0.9219	3-3/4"	5-3/4"	R/L059
15/16"	0.9375	3-3/4"	5-3/4"	R/L060
61/64"	0.9531	3-7/8"	5-7/8"	R/L061
31/32"	0.9688	3-7/8"	5-7/8"	R/L062
63/64"	0.9844	4"	6"	R/L063
1"	1.0000	4"	6"	R/L100
1-1/32"	1.0312	4"	6-1/4"	R/L102
1-1/16"	1.0625	4" 4"	6-1/4"	R/L104
1-3/32"	1.0938	4"	6-3/8"	R/L106
1-1/8"	1.1250	4"	6-3/8"	R/L108
1-5/32"	1.1562	4-1/4"	6-5/8"	R/L110
1-3/16"	1.1875	4-1/4"	6-5/8"	R/L112
1-7/32"	1.2188	4-3/8"	6-3/4"	R/L114
1-1/4"	1.2500	4-3/8"	6-3/4"	R/L116
1-9/32"	1.2812	4-3/8"	7"	R/L118
1-5/16"	1.3125	4-3/8"	7"	R/L120
1-11/32"	1.3438	4-1/2"	7-1/8"	R/L122
1-3/8"	1.3750	4-1/2"	7-1/8"	R/L124
1-13/32"	1.4062	4-3/4"	7-3/8"	R/L126
1-7/16"	1.4375	4-3/4"	7-3/8"	R/L128
1-15/32"	1.4688	4-7/8"	7-1/2"	R/L130
1-1/2"	1.5000	4-7/8"	7-1/2"	R/L132
1-17/32"	1.5312	4-7/8"	7-3/4"	R/L134
1-9/16"	1.5625	4-7/8"	7-3/4"	R/L136
1-19/32"	1.5938	4-7/8"	7-3/4"	R/L138
1-5/8"	1.6250	4-7/8"	7-3/4"	R/L140
1-21/32"	1.6562	5-1/8"	8"	R/L142
1-11/16"	1.6875	5-1/8"	8"	R/L144
1-23/32"	1.7188	5-1/8"	8"	R/L146
1-3/4"	1.7500	5-1/8"	8"	R/L148
1-25/32"	1.7812	5-3/8"	8-1/4"	R/L150
1-13/16"	1.8125	5-3/8"	8-1/4"	R/L152
1-27/32"	1.8438	5-3/8"	8-1/4"	R/L154
1-7/8"	1.8750	5-3/8"	8-1/4"	R/L156
1-29/32"	1.9062	5-5/8"	8-1/2"	R/L158
1-15/16"	1.9375	5-5/8"	8-1/2"	R/L160
2"	2.0000	5-5/8"	8-1/2"	R/L200
2-1/16"	2.0625	5-5/8"	8-1/2"	R/L204
2-1/8"	2.1250	5-5/8"	8-1/2"	R/L208
2-3/16"	2.1875	5-5/8"	8-1/2"	R/L212
2-1/4"	2.2500	5-5/8"	8-1/2"	R/L216
2-3/8"	2.3750	5-5/8"	8-1/2"	R/L224
2-1/2"	2.5000	5-5/8"	8-1/2"	R/L232

## Wire Gauge Sizes

Size	Dec. Equiv	Flute Length	Overall Length	List No
1	0.2280	1-5/16"	2-7/16"	RN01
2	0.2210	1-5/16"	2-7/16"	RN02

Size	Dec. Equiv	Flute Length	Overall Length	List No
31	0.1200	7/8"	1-7/8"	RN31
32	0.1160	7/8"	1-7/8"	RN32

# TopTech Tool Manufacturing Inc.



## **Screw Machine Length Drills**

## Wire Gauge Sizes

				Wire Gauge
Size	Dec. Equiv	Flute	Overall	List No
3	0.2130	Length 1-1/4"	<b>Length</b> 2-3/8"	RN03
4	0.2090	1-1/4"	2-3/8"	RN04
5	0.2055	1-1/4"	2-3/8"	RN05
6	0.2040	1-1/4"	2-3/8"	RN06
7	0.2010	1-3/16"	2-1/4"	RN07
8	0.1990	1-3/16"	2-1/4"	RN08
9	0.1960	1-3/16"	2-1/4"	RN09
10	0.1935	1-3/16"	2-1/4"	RN10
11	0.1910	1-3/16"	2-1/4"	RN11
12	0.1890	1-3/16"	2-1/4"	RN12
13	0.1850	1-1/8"	2-3/16"	RN13
14	0.1820	1-1/8"	2-3/16"	RN14
15	0.1800	1-1/8"	2-3/16"	RN15
16	0.1770	1-1/8"	2-3/16"	RN16
17	0.1730	1-1/8"	2-3/16"	RN17
18	0.1695	1-1/16"	2-1/8"	RN18
19	0.1660	1-1/16"	2-1/8"	RN19
20	0.1610	1-1/16"	2-1/8"	RN20
21	0.1590	1-1/16"	2-1/8"	RN21
22	0.1570	1-1/16"	2-1/8"	RN22
23	0.1540	1"	2-1/16"	RN23
24	0.1520	1"	2-1/16"	RN24
25	0.1495	1"	2-1/16"	RN25
26	0.1470	1"	2-1/16"	RN26
27	0.1440	1"	2-1/16"	RN27
28	0.1405	15/16"	1-15/16"	RN28
29	0.1360	15/16"	1-15/16"	RN29
30	0.1285	15/16"	1-15/16"	RN30

Size	Dec. Equiv	Flute Length	Overall Length	List No
33	0.1130	7/8"	1-7/8"	RN33
34	0.1110	7/8"	1-7/8"	RN34
35	0.1100	7/8"	1-7/8"	RN35
36	0.1065	13/16"	1-13/16"	RN36
37	0.1040	13/16"	1-13/16"	RN37
38	0.1015	13/16"	1-13/16"	RN38
39	0.0995	13/16"	1-13/16"	RN39
40	0.0980	13/16"	1-13/16"	RN40
41	0.0960	13/16"	1-13/16"	RN41
42	0.0935	3/4"	1-3/4"	RN42
43	0.0890	3/4"	1-3/4"	RN43
44	0.0860	3/4"	1-3/4"	RN44
45	0.0820	3/4"	1-3/4"	RN45
46	0.0810	3/4"	1-3/4"	RN46
47	0.0785	11/16"	1-11/16"	RN47
48	0.0760	11/16"	1-11/16"	RN48
49	0.0730	11/16"	1-11/16"	RN49
50	0.0700	11/16"	1-11/16"	RN50
51	0.0670	11/16"	1-11/16"	RN51
52	0.0635	11/16"	1-11/16"	RN52
53	0.0595	5/8"	1-5/8"	RN53
54	0.0550	5/8"	1-5/8"	RN54
55	0.0520	5/8"	1-5/8"	RN55
56	0.0465	1/2"	1-3/8"	RN56
57	0.0430	1/2"	1-3/8"	RN57
58	0.0420	1/2"	1-3/8"	RN58
59	0.0410	1/2"	1-3/8"	RN59
60	0.0400	1/2"	1-3/8"	RN60

## **Letter Sizes**

Size	Dec. Equiv	Flute Length	Overall Length	List No
Α	0.2340	1-5/16"	2-7/16"	RL0A
В	0.2380	1-3/8"	2-1/2"	RL0B
С	0.2420	1-3/8"	2-1/2"	RL0C
D	0.2460	1-3/8"	2-1/2"	RL0D
Ε	0.2500	1-3/8"	2-1/2"	RL0E
F	0.2570	1-7/16"	2-5/8"	RL0F
G	0.2610	1-7/16"	2-5/8"	RL0G
Н	0.2660	1-1/2"	2-11/16"	RL0H
1	0.2720	1-1/2"	2-11/16"	RL0I
J	0.2770	1-1/2"	2-11/16"	RL0J
K	0.2810	1-1/2"	2-11/16"	RL0K
L	0.2900	1-9/16"	2-3/4"	RL0L
М	0.2950	1-9/16"	2-3/4"	RL0M

Size	Dec. Equiv	Flute Length	Overall Length	List No
N	0.3020	1-5/8"	2-13/16"	RL0N
0	0.3160	1-11/6"	2-15/16"	RL0O
Р	0.3230	1-11/6"	2-15/16"	RL0P
Q	0.3320	1-11/16"	3"	RL0Q
R	0.3390	1-11/16"	3"	RL0R
S	0.3480	1-3/4"	3-1/16"	RL0S
Т	0.3580	1-3/4"	3-1/16"	RL0T
U	0.3680	1-13/16"	3-1/8"	RL0U
V	0.3770	1-7/8"	3-1/4"	RL0V
W	0.3860	1-7/8"	3-1/4"	RL0W
Χ	0.3970	1-15/16"	3-5/16"	RL0X
Υ	0.4040	1-15/16"	3-5/16"	RL0Y
Z	0.4130	2"	3-3/8"	RL0Z

www.toptechtool.com

sales@toptechtool.com